

**THE TANK™ S**

**COMMERCIAL  
ZERO-TURN  
MOWERS WITH  
SYNCHRO STEER™  
TECHNOLOGY**

THE TANK™ S6031

THE TANK™ S7237

**FEATURES**

SELECT CUT  
SYSTEM™ DECK

CUTS UP TO 7.5  
ACRES PER HOUR

FULLY HYDRAULIC  
POWER STEERING

HYDRAULIC POWER  
DECK LIFT

3-WAY ADJUSTABLE  
STEERING COLUMN

REMOTE COOLING  
SYSTEM

PROVEN TANK™  
PLATFORM

31 AND 37 HP\* OPTIONS  
WITH 60" AND 72"  
DECKS

ATTACHMENTS  
AVAILABLE

**COMMERCIAL**  
MOWING  
EQUIPMENT



**WE MEAN BUSINESS.™**



**WITH MORE STABILITY, MANEUVERABILITY AND CONTROL,  
GETTING THE JOB DONE IS EVEN EASIER.**

Introducing THE TANK™ S, the revolutionary zero-turn mower with patented Synchro Steer™ technology. Our intuitive steering wheel control provides complete control of the front wheels, which makes this zero-turn more maneuverable and stable on any terrain — even on steep hills. And the safer and more confident the operators feel, the more productive they can be. It's also more attachment-friendly, so it can do a whole lot more than just cut grass. THE TANK™ S is easily the most productive mower available, and everyone knows that more production leads to more profit.


**SIMPLE TO OPERATE**

Even an inexperienced operator can safely and confidently operate THE TANK™ S because of intuitive controls — like a fully adjustable steering wheel with power steering and forward and reverse foot pedals. Plus, it comes equipped with an adjustable air ride suspension seat with lumbar support and arm rests to reduce operator fatigue and increase productivity.



**SELECT CUT  
SYSTEM™ DECK**

Equipped with a sloped-nose front skirt and an adjustable leading edge to adjust the vacuum, configurable inner baffle to control the airflow and discharge, ball wheels to eliminate scalping, offset edge for more efficient trimming, adjustable striping roller for a clean finish and patented SmartJet™ deck wash system for easy cleanup, it's no wonder this is the most innovative deck on the market.



**STABILITY AND  
MANEUVERABILITY,  
EVEN ON HILLS**

Patented Synchro Steer™ technology gives the operator full directional control of the front wheels, unlike the free-rotating front casters of standard zero-turns. This provides full stability on hillsides, even steep areas that previously required a walk-behind. THE TANK™ S makes true zero-degree turns and tight maneuvers around any obstacle, while virtually eliminating the potential for turf damage.



\*as rated by engine manufacturer



# COMMERCIAL ZERO-TURN MOWERS



ENGINE	THE TANK™ S6031	THE TANK™ S7237
Engine type	31 HP* Kawasaki® V-Twin OHV	37 HP* Kawasaki® V-Twin OHV
Engine displacement/orientation	852cc/vertical	999cc/vertical
Engine fuel	Gas	
Ignition	Capacitor discharge ignition (CDI)	
Lubrication/filter	Full pressure w/spin-on oil filter	
Cooling system	Air	
Air cleaner	Heavy-duty remote — replaceable dual element	
Alternator	12V-20 amp. regulated	
Fuel capacity	Twin 7-gallon tanks	
<b>DRIVE SYSTEM</b>		
Drive system	Dual Hydro-Gear™ BDP-12 pumps and White® wheel motors	
Ground speed	Fwd: 12 mph/Rev: 5 mph	
Hydraulic fluid	Rimula — 15W40 and remote cooling system	
Hydro fluid capacity	6 qt.	
Hydraulic oil filter	Standard, 25 micron cartridge type	
Controls	Individual forward, reverse and park brake foot pedals	
Lock to lock turns (steering wheel)	2 turns/multi-position steering wheel and column	
Braking/parking brake	Expansion shoe/drum	
<b>STEERING</b>		
Power steering (front wheels)	Fully hydraulic power steering w/Synchro Steer™ technology	
Front axle	Pivoting	
<b>CHASSIS</b>		
Frame	Fabricated, heavy-duty tubular steel	
<b>TIRES</b>		
Front tire size	16" x 6.5" - 8" (Turf Trac R/S)	
Rear tire size	24" x 12" - 12" (Turf Master®)	
<b>DIMENSIONS</b>		
Length x width x height	89" x 62" x 72"	89" x 74" x 72"
Wheelbase	54"	
Front tread centers	42"	
Rear tread centers	45.1"	
Weight (approx.)	1,470 lbs.	1,540 lbs.
<b>MOWING</b>		
Deck size/type	60" Select Cut System™	72" Select Cut System™
Deck style/system	6-point suspension, full floating	
Deck blades	Three 21" high lift with extended cutting edge	Three 25" high lift with extended cutting edge
Deck construction	10-gauge fabricated with 7-gauge steel skirt, 3/8" rub guard, 1/4" adjustable leading edge and 7- and 10-gauge reinforcements at spindle assemblies	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
Deck lift	Dash-mount control lever w/hydraulic lift system	
Deck height adjustment	1" - 5" (in .25" increments)	
Blade spindle construction	Durable machined cast-aluminum housing w/greasable tapered roller bearings	
PTO engagement	Ogura GT 3.5/250 ft. lb.	
Anti-scalping wheels	4 standard, greasable	6 standard, greasable
Rear anti-scalping rollers/striper	Full width, adjustable	
Deck PTO	Electronic fingertip engagement	
<b>ADDITIONAL SPECIFICATIONS</b>		
ROPS	Foldable (OSHA-1928 compliant)	
Monitor/hour meter	Standard, hour/tachometer/maintenance minder	
Seat type/motion range front/rear	Fully adjustable suspension, lumbar and arm rests and reclining back w/8.25" of travel	
Cup holder	Accommodates multiple-size containers	
Storage pouch	Standard	
Rear hitch	Standard	
<b>WARRANTY*</b>		
	3-year commercial	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

\*as rated by engine manufacturer † See your local Cub Cadet Independent Dealer for warranty details. Commercial products are intended for professional use.

773-03691 Printed in U.S.A. 12/08 © 2009 Cub Cadet